

FITLERS WITH BAYONET

DESCRIPTION

- Combined filter with bayonet connection for A2P3R organic gases and vapours with boiling point above 65°C, and fine toxic dusts, fumes, and mists.
- Quick bayonet release
- Must be used only by pair with ETNA (6ETN200NSI) & PANAREA TWIN (6PAN200NSI)
- Body of the cartridge in ABS
- Filtering material : active carbon and filtering non-woven PP.

SECTORS

Heavy industry

Light industry

Infrastructure, building industry

Transport and logistics

A2P3R

The +

- Organic gas and vapours with boiling point > 65°C and fine toxic dusts
- For regular and prolonged use in a dangerous environment: industrial maintenance, Fertilizer spreading, chemical industry, paint application, carpentry, wood industry, cementindustry, metal cutting ...

PACKAGING

72 Pieces / Carton



X4



Boxes

TECHNICAL FEATURES

Weight	132 g	Features	Filtering material : active carbon and filtering non-woven PP.
Performance	Breathing resistance : • 15 l/min : 1,45 mbar. • 47,5 l/min : 5,10 mbar. • Class 2 according to EN14387:2004	Fields of application	A2P3R organic gases and vapours with boiling point above 65°C, and fine toxic dusts, fumes, and mists. Organic gas and vapours with boiling point > 65°C and fine toxic dusts For regular and prolonged use in a dangerous environment: industrial maintenance, Fertilizer spreading, chemical industry, paint application, carpentry, wood industry, cement industry, metal cutting ... Do not use in a place where oxygen concentration is less than 17 vol. %
Main risk	Aerosols and gases and vapours		

LEGISLATION

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **PPE060AT1696**.
Delivered by **ITALCERT (0426)**.

EN14387:2004+A1:2008

Gas filters and combined filters

EN143:2000+A1:2006

Particles filters

Retailer stamp